


CORP. STOP	TYPE 1 & 2	TYPE 3 & 4 F1000G H15006	
FORD	Ff100G		
MUELLER	H15024		



NOTES:

- 1. TYPE 1-INSTALL ANODE AS SHOWN IN STANDARD DETAIL W-15.
- 2. TYPES 1 & 2-WRAP CORPORATION STOP AND 5' OF COPPER TUBING WITH 10 MIL PVC TAPE (1/2 LAPPED).
- 3. TYPE 1-IF WATER MAIN IS COATED, REPLACE COATING ON MAIN AND COAT WELD-ON SERVICE SADDLE AND INSUL-ATING BUSHING WITH 1/4" MIN. COATING OF SAME MATERIAL (OR 10 MIL PVC TAPE)
- 4. TYPE 2- IF MAIN IS POLYWRAPPED, REPAIR AND EXTEND POLYWRAP TO COVER CORPORATION STOP.
- 5. FOR WATER METER INSTALLATION SEE STANDARD DETAIL W-2.
- 6. ALL BRASS CORPS FOR BRASS SADDLES SHALL HAVE CC THREADS (SADDLES AND CORPS)

	SE	RVICE CONNEC	TION SCHEDUL	E		
SERVICE	WATER MAIN MATERIAL					
SIZE	STEEL	D.I.P.	A.C.P.	R.P.M.	P.V.C.	
3/4"	TYPE 1	TYPE 2	TYPE 3	TYPE 3	TYPE 4	
17	n		•	"	н	
1- 1/2"	И	•	4	п	"	
2*	u '	n		н	и	

APPROVED BY

well

CONNECTION TYPES FOR 3/4" - 2" SERVICE TAPS

DEPARTMENT OF PUBLIC WORKS

DRAWING NO.

W_1